DT66

Enterprise Mobile Computer

- 6.5-inch ultra-high-definition (720*1600) thin-bezel display, offers more information at one page and less scrolling.
- Supports in-display and backside NFC reading to meet diverse usage needs.
- The 5000mAh smart battery with a built-in battery management system enhancing overall battery life. With the hot swap feature, it achieves uninterrupted 24-hour operation.
- Powered by the latest Qualcomm 2.4GHz high-performance processor, it delivers exceptional processing speed, further empowering faster decoding of 1D/2D/DPM barcode.
- Wi-Fi 6E and 5G delivers the super fast and reliable wireless connections.
- Optional iToF camera for three-dimensional volume measurement of parcel.







Processor

Android 13

O.S.



Sealing



Display



5000mAh Smart Battery

Optional Accessories:







Trigger Handle

4-Slot Battery Charging Cradle

Charging Cradle

DT66 Enterprise Mobile Computer Specifications





Octa-core 2.4 GHz



Android 13, upgradable to Android 18 Support GMS/AER

Memory

RAM: 4GB ROM: 64GB RAM: 8GB ROM: 128GB (optional) Micro-SD card, Up to 256 GB


□ Display

6.5 inch display, 720*1600

Touch Screen

Ultra sensitive capacitive touch panel, support multi-touch, works with gloves and wet fingers

175.8 mm L x 76.5 mm W x 14.5 mm D Weight: About 283g



Professional scan engine Support international standard 1D/2D barcode; Support barcode displayed on screen

Camera

Front: 5MP FF; Rear: 13MP PDAF Optional iToF camera

Sensors

Light + Accelerator+ Proximity + Geomagnetic + Gyro+ Pressure(optional)

口》Audio

Dual-Microphone with noise cancellation, 1.5W speaker for loud noise, reciever supports echo cancellation

Battery

Capacity: 3.85V 5000mAh Support hot swap

Buttons

PWR button Vol +/- button Scan button*2 Custom button

Slots

Nano- SIM x 2, Micro-SD Slot x 1, (Reserved support eSIM)

Communication

5G/4G/3G/2G Bluetooth: BT5.2 + BR/EDR + BLE Wi-Fi: Wi-Fi 6E, 2.4G/5G Support 2x2 MU-MIMO,

IEEE 802.11a/b/g/n/ac/d/e/h/i/k/r/v/w/ax

Roaming: 802.11r

(Over the Air);OKC/;PMKID caching

O Positioning

GPS BEIDOU GLONASS Galileo

Protection

1.5m drop resistance

Operating Temp.: -20 ~ +60°C Storage Temp.: -40 ~ +70°C

Humidity: 5%RH ~ 95%RH(No condensation)

ESD: +/-15kv Air: +/-8kv contact

UROVO PTE. LIMITED

Website: en.urovo.com Email: urovo@urovo.com Address: 1 Raffles Place, #21-01 One Raffles Place Tower 1, Singapore 048616

Urovo Europe

Website: europe.urovo.com Email: sales-europe@urovo-emea.com Address: de Maas 9, 5684PL, Best, the Netherlands

*This page is subject to change without prior notice

Website: us.urovo.com Email: urovo@urovo.com

Urovo North America

Address: 1990 Main Street, Suite 750, Sarasota,

Florida 34236